





- > Compacy & High Line Array
- > Clear Vocal Reproduction



High Power Compact Dual 8 Inch Line Array 2-Way Line Array System



Power Capacity (AES Standards) RMS Program

Frequency Response

**Output Sensitivity** 

**Impedance** 

**High Pass Filter** 

**Recommended Application** 


**Woofer Section** 

**High Driver** 

Recommended Signal Processing Box Construction

Grille

**Input Connectors** 



700 Watt 1400 Watt 65Hz (-10Db) to 18500Hz

102 dB, 1Meter/Watt 142dB, 1Meter/Watt (SPL MAX)

8Ω/Cabinet

35Hz/ 48dB/ Butterworth

PUB, Church, Mosque, Live Band, Small to medium size venue

Woofer 8" midbass STA 8 CS(4Ωx2) 350 Watt AES, 2" voice coil

DE920 x 16Ω x 1 unit, Neo Driver 110 Watt AES 1.4 inch Throat with 3 inch Composite Material Voice Coil

65Hz to 18.5KHz (Indoor) 95Hz to 18.5KHz (Outdoor)

Plywood 12mm Weather Proof Material & Resin Coated with Sandtexture Weather Resistance Paint Matte Black Finish

Black Powder Coat Peforated Metal Grill with Weather Proof Nylon + Foam Cloth

Speedcon® NL-8 (2x) Pins 1 +/- & 2 +/-

Net Weight: 33 kgs